

DECO-STAMP

ACRYLIC EMULSION BASED STAMP EFFECT DECORATIVE PAINT

DEFINITION

Acrylic emulsion based, waterborne, stamp effect decorative top coat paint.

PROPERTIES

DECO-STAMP is at paint viscosity and used to obtain different architectural patterns with different properties and different effects. The general properties;

- Flexible
- Easy-to-use
- Different colour reflection at different sight angles
- High UV resistant
- Low water absorption

AREAS OF APPLICATION

DECO-STAMP can be used on all interior walls for different architectural effects.

SURFACE PREPARATION

New surfaces: The surface should be cleaned of dust, stain, and impurities. Decopaste group putty should be used to maintain a smooth satin surface. Dekonar and Decopaste are recommended for the repairment of the surfaces.

Old surfaces: The surface should be cleaned of dust, stain, grease, impurities, and loose and swelled layers. Dekonar and Decopaste are recommended for the repairment of the surfaces.

APPLICATION

DECOSTAMP should be transferred on the surface by brush or roller smoothly. Before the drying the decorative tools (sponge, chamois, shammy leather etc) should be treated for the stamp effect according to the painter's visual pleasure.

PACKAGING AND STORAGE

DECO-STAMP is produced in 15 / 7,5 / 5 / 2,5 kg plastic pails. The goods should be stored in clean and dry areas and kept away from sun, rain, hot and cold weathers. The unsealed goods can be stored for 12 months.

HEALTH AND SECURITY

S2 Keep out of reach of children.

DECO-STAMP

ACRYLIC EMULSION BASED STAMP EFFECT DECORATIVE PAINT

TECHNICAL DATA

Consumption:	Depending on the pattern and surface properties 0,050 - 0,150 kg/m ²	
Viscosity	100-120 KU	TAL-058
Density	1,01 ±0,03 g/cm ³	TAL- 001
pH	8-9	TAL- 004